IPTI

Section I. (Amendments to the Claims and Listing of Claims)

Please amend claims 1-4, 6-7, 10, 12-22, 24-26, 35-36, 38-39 and 42-45 as set out below. Claims 1-4, 6-7, 10, 12-22, 24-26, 31-36, and 38-45 are pending as set forth below.

- 1. (Currently amended) A method of forming an iridium-containing film on a substrate, comprising use of an organic solvent solution, said organic solvent solution comprising an iridium containing precursor that is decomposable to deposit iridium on the substrate, said method comprising the steps of:
- (a) decomposing the precursor from said solution an iridium containing precursor provided in an organic solvent, and
- wherein the decomposition of the precursor and deposition of iridium on the substrate is said steps (a) and (b) are carried out by a process selected from the group consisting of chemical vapor deposition (CVD), assisted-CVD, ion plating, rapid thermal processing, and molecular beam epitaxy.
- 2. (Currently amended) A-The method according to claim 1, wherein the oxidizing ambient environment comprises an atmosphere containing an oxidizing gas selected from the group consisting of oxygen, ozone, air, and nitrogen oxide.
- (Currently amended) A-<u>The</u> method according to claim 1, wherein the iridium deposited on the substrate in said step (b) comprises elemental iridium.
- 4. (Currently amended) A-The method according to claim 1, wherein the iridium deposited on the substrate in said step (b) comprises iridium oxide, or a combination of elemental iridium and iridium oxide.
- 5. (Cancelled)
- 6. (Currently amended) A-The method according to claim 31, wherein the coordinating Lewis base is selected from the group consisting of alkene, diene, cycloalkene, cycloalken

7. (Currently amended) A-The method according to claim 1, wherein the oxidizing ambient environment comprises air.

8.-9. (Cancelled)

IPTL

10. (Currently amended) A—The method according to claim 32, wherein the coordinating Lewis base is selected from the group consisting of alkene, diene, cycloalkene, cycloalke

11. (Cancelled)

- 12. (Currently Amended) A—The method according to claim 33, wherein the coordinating Lewis base is selected from the group consisting of alkene, diene, cycloalkene, cycloalke
- 13. (Currently amended) A-The method according to claim 1, wherein the decomposition of the precursor and deposition of iridium on the substrate is said steps (a) and (b) are carried out by chemical vapor deposition.
- 14. (Currently amended) A-<u>The</u> method according to claim 1, wherein the iridium deposited on the substrate in said step (b) is processed to <u>yield-form</u> an iridium-containing film element on the substrate, having critical dimensional characteristics below about 0.5 micron.
- 15. (Currently amended) A-The method according to claim 14, wherein the decomposition of the precursor and deposition of iridium on the substrate is are carried out by chemical vapor deposition.
- 16. (Currently amended) A method of forming a microelectronic device or <u>a precursor</u> structure on a substrate, including an electrode operatively associated with a high-temperature

dielectric or a high-temperature ferroelectric material deposited thereover, said method comprising the steps of:

- (A) forming an iridium-containing film on the substrate, comprising use of an organic solvent solution, said organic solvent solution comprising from an iridium-containing precursor provided in an organic solvent, wherein the precursor which is decomposable to deposit iridium on the substrate, and further comprising:
- (i) decomposing the precursor from said solution and depositing iridium on the substrate in an oxidizing ambient environment, wherein the decomposition of the precursor and deposition of iridium on the substrate is are carried out by a process selected from the group consisting of chemical vapor deposition (CVD), assisted-CVD, ion plating, rapid thermal processing, and molecular beam epitaxy; and
- (ii) processing the deposited iridium into an iridium-based electrode element; and
- (B) depositing on the iridium-based electrode element a high temperature dielectric material, a high temperature -and/or-ferroelectric material or both.
- 17. (Currently amended) A-The method according to claim 16, wherein the iridium-based electrode element has deposited thereon a high temperature dielectric material.
- 18. (Currently amended) A-The method according to claim 16, wherein the iridium-based electrode element has deposited thereon a high temperature ferroelectric material selected from the group consisting of SBT and PZT.
- 19. (Currently amended) A-The method according to claim 16, wherein the microelectronic device or the precursor structure on the substrate comprises a DRAM or a FRAM capacitor device or structure.
- 20. (Currently amended) A-The method according to claim 16, wherein the high temperature dielectric, <u>and/or-the high temperature</u> ferroelectric material <u>or both comprises</u> a material selected from the group consisting of SBT, PZT, BST, PLZT, PNZT, and LCMO.
- 21. (Currently <u>a</u>Amended) A—<u>The</u> method according to claim 16, wherein the iridium deposited on the substrate comprises elemental iridium.

22. (Currently amended) A-The method according to claim 16, wherein the iridium deposited on the substrate comprises iridium oxide or a combination of elemental iridium and iridium oxide.

23. (Cancelled)

- 24. (Currently amended) A-The method according to claim 34, wherein the coordinating Lewis base is selected from the group consisting of alkene, diene, cycloalkene, cycloalke
- 25. (Currently amended) A—The method according to claim 34, wherein the oxidizing ambient environment comprises air.
- 26. (Currently amended) A-The method according to claim 16, wherein steps (A)(i), (A)(ii) and (B) are carried out in the same oxidizing ambient environment.

27.-30. (Cancelled)

31. (Previously presented) A method of forming an iridium-containing film on a substrate, comprising use of an organic solvent solution, said organic solvent solution comprising an iridium-containing precursor that is decomposable to deposit iridium on the substrate, said method comprising decomposing the precursor from said solution and depositing iridium on the substrate in an oxidizing ambient environment, wherein the precursor comprises a composition selected from the group consisting of:

Lewis base stabilized Ir(I) B-diketonates of formula I:

wherein R and R' may be alike or different and may be H, aryl, perfluoroaryl, C₁ - C₆ alkyl, or C₁ - C₆ perfluoroalkyl, and L is a coordinating Lewis base; and

Lewis base stabilized Ir(I) B-ketoiminates of formula II:

wherein R, R', and R" are the same or different, and are independently selected from the group consisting of H, aryl, perfluoroaryl, C₁ - C₆ alkyl, or C₁ - C₆ perfluoroalkyl, and L is a coordinating Lewis base.

32. (Previously presented) A method of forming an iridium-containing film on a substrate, from an iridium-containing precursor thereof that is decomposable to deposit iridium on the substrate, said method comprising decomposing the precursor and depositing iridium on the substrate in an oxidizing ambient environment, wherein the precursor comprises a composition selected from the group consisting of:

Lewis base stabilized Ir(I) \(\beta\)-diketonates of formula I:

wherein R and R' may be alike or different and may be H, aryl, perfluoroaryl, C₂ - C₆ alkyl, or C₁ - C₆ perfluoroalkyl, and L is a coordinating Lewis base.

33. (Previously presented) A method of forming an iridium-containing film on a substrate, from an iridium-containing precursor thereof that is decomposable to deposit iridium on the substrate, said method comprising decomposing the precursor and depositing iridium on the substrate in an oxidizing ambient environment, wherein the precursor comprises a composition selected from the group consisting of:

8 /28

IPTL

Lewis base stabilized Ir(I) \(\beta\)-ketoiminates of formula II:

wherein R, R', and R" are the same or different, and are independently selected from the group consisting of H, aryl, perfluoroaryl, C_1 - C_6 alkyl, or C_1 - C_6 perfluoroalkyl, and L is a coordinating Lewis base.

- 34. (Previously presented) A method of forming a microelectronic device or precursor structure on a substrate, including an electrode operatively associated with a high-temperature dielectric or ferroelectric material deposited thereover, said method comprising:
- (A) forming an iridium-containing film on the substrate, comprising use of an organic solvent solution, said organic solvent solution comprising an iridium-containing precursor which is decomposable to deposit iridium on the substrate, comprising:
- (i) decomposing the precursor from said solution and depositing iridium on the substrate in an oxidizing ambient environment; and
- (ii) processing the deposited iridium into an iridium-based electrode element; and
- (B) depositing on the iridium-based electrode element a high temperature dielectric and/or ferroelectric material,

wherein the iridium-containing precursor comprises a composition selected from the group consisting of:.

Lewis base stabilized Ir(I) \(\beta\)-diketonates of formula I:

1

wherein R and R' may be alike or different and may be H, aryl, perfluoroaryl, C₁ - C₆ alkyl, or C₁ - C₆ perfluoroalkyl, and L is a coordinating Lewis base; and

Lewis base stabilized Ir(I) B-ketoiminates of formula II:

wherein R, R', and R" are the same or different, and are independently selected from the group consisting of H, aryl, perfluoroaryl, C₁ - C₆ alkyl, or C₁ - C₆ perfluoroalkyl, and L is a coordinating Lewis base.

- 35. (Currently amended) A method of forming an iridium-containing film on a substrate, comprising use of an organic solvent solution, said-organic solvent solution comprising an iridium (I) containing precursor that is decomposable to deposit iridium on the substrate, said method comprising the steps of:
- (a) ____decomposing the precursor from said solution an iridium (1) containing precursor provided in an organic solvent, and
- (b) ____depositing iridium on the substrate in an oxidizing ambient environment, _ wherein the decomposition of the precursor and deposition of iridium on the substrate said steps (a) and (b) is are carried out by a process selected from the group consisting of chemical vapor deposition (CVD), assisted-CVD, ion plating, rapid thermal processing, and molecular beam epitaxy.
- 36. (Currently amended) A method of forming a microelectronic device or <u>a precursor</u> structure on a substrate, including an electrode operatively associated with a high-temperature dielectric or <u>a high-temperature</u> ferroelectric material deposited thereover, said method comprising the steps of:
- (A) forming an iridium-containing film on the substrate, comprising use of an organic solvent solution, said organic solvent solution comprising from an iridium (I)-containing precursor provided in an organic solvent, wherein the precursor which is decomposable to deposit iridium on the substrate, and further comprising:

- (i) decomposing the precursor from said solution and depositing iridium on the substrate in an oxidizing ambient environment, wherein the decomposition of the precursor and deposition of iridium on the substrate is are carried out by a process selected from the group consisting of chemical vapor deposition (CVD), assisted-CVD, ion plating, rapid thermal processing, and molecular beam epitaxy; and
- (ii) processing the deposited iridium into an iridium-based electrode element; and
- (B) depositing on the iridium-based electrode element a high temperature dielectric material, a high temperature and/or-ferroelectric material or both.

37. (Cancelled)

IPTL

- 38. (Currently amended) The method of claim 1, wherein said organic solvent solution comprises a non-polar solvent selected from the group consisting of C_5 - C_{12} hydrocarbon alkanes and C_6 - C_{10} hydrocarbon aryls.
- 39. (Currently amended) The method of claim 16, wherein said organic solvent solution comprises a non-polar solvent selected from the group consisting of C_5 - C_{12} hydrocarbon alkanes and C_6 - C_{10} hydrocarbon aryls.
- 40. (Previously presented) The method of claim 31, wherein said organic solvent solution comprises a non-polar solvent selected from the group consisting of C_5 - C_{12} hydrocarbon alkanes and C_6 - C_{10} hydrocarbon aryls.
- 41. (Previously presented) The method of claim 34, wherein said organic solvent solution comprises a non-polar solvent selected from the group consisting of C_5 - C_{12} hydrocarbon alkanes and C_6 - C_{10} hydrocarbon aryls.
- 42. (Currently amended) The method of claim 35, wherein said organic solvent solution comprises a non-polar solvent selected from the group consisting of C_5 - C_{12} hydrocarbon alkanes and C_6 - C_{10} hydrocarbon aryls.

- 43. (Currently amended) The method of claim 36, wherein said organic solvent solution comprises a non-polar solvent selected from the group consisting of C_5 - C_{12} hydrocarbon alkanes and C_6 - C_{10} hydrocarbon aryls.
- 44. (Currently amended) The method according to claim 1, wherein the organic solvent solution comprises an organic solvent selected from C₆-C₁₂ alkane solvents, benzene, C₁-C₈ alkyl-substituted benzene solvents, toluene, carbon tetrachloride, chloroform, methylene chloride, or diethylether, tetrahydrofuran.
- 45. (Currently amended) The method according to claim 1, wherein if the iridium-containing precursor is cyclooctadiene adduct of Ir(I) beta-diketonate, then the organic solvent solution-does not include an alkanolic solvent-as an organic solvent.

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

BLACK BORDERS

IMAGE CUT OFF AT TOP, BOTTOM OR SIDES

FADED TEXT OR DRAWING

BLURRED OR ILLEGIBLE TEXT OR DRAWING

SKEWED/SLANTED IMAGES

COLOR OR BLACK AND WHITE PHOTOGRAPHS

GRAY SCALE DOCUMENTS

LINES OR MARKS ON ORIGINAL DOCUMENT

REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

IMAGES ARE BEST AVAILABLE COPY.

OTHER:

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.